

# PLYCO

CORPORATION  
PO BOX 386 • ELKHART LAKE, WI 53020

## EQUUS DUTCH DOOR SYSTEMS

---

*Delivered Pre-Assembled or KD*

*Designed with Horse Safety in Mind*

*Extended Jamb Available*

*Heavy Duty Hinges are Extra Strong  
and Bolt into the Door Panel*

*Door Panel Perimeters are Cut and  
Formed from a Single Piece of 16  
Gauge Steel*

**EQUUS  
DUTCH DOOR SYSTEMS**







## EQUUS Dutch Doors

- Pre-Assembled Door Panels with Matching Crossbucks Assembled over Matching or Contrasting Steel Sheet
- Door Panel Perimeters are Cut and Formed from a Single Piece of 16 gauge steel
- Paint System is Quality Powder Coat Urethane over a Six Stage Pre-Wash
- Heavy Duty Hinges are Extra Strong and Bolt into the Door Panel
- For Professional Installations, a 16 gauge Pre-Punched Steel Jamb and Header System is Available

## Crossbucks

- Formed with the same 16 gauge steel, then powder coat painted to match the door frame and assembled into the Dutch Door. Matching screws secure each corner and the center of the crossbuck providing a decorative finish and adding strength.



## Barrel Bolt

- On the inside of the door connects the two door halves together to operate as a single door.

## Standard Jamb (Optional)



## Dutch Door Hinge

- Designed to be extra strong and horse safe. The large hinge half that attaches to the building has rounded corners that will not hurt a horse rubbing in passing. All hinges are "E" coated for corrosion resistance, then powder coat painted to match the door. The door hinge half is mostly concealed inside and bolts directly to the door panel. Two slotted holes in the jamb hinge half allow adjustment when the door is installed without the EJS-4700 steel jamb kit and two round holes assure sag-free final installation with or without the steel jamb.



## Optional Dutch Door Latch Kit

- Prevents horse injury while adding extra security. Designed & engineered for most types of swing door systems. Double sided easy operation. Heavy duty Stainless Steel and easy installation.



## Extended Jamb (Optional)

- Includes hinge side, strike side, and header. All pieces are formed using 16 gauge steel then powder coat painted with the same colors available for the Dutch Door components. All pieces are pre-punched with mounting holes and the hinge jamb piece is pre-punched for hinge holes to mate with the AP-4700 Dutch Door. The jamb kit provides a strong, finished appearance and helps eliminate door sag.



## Bale Door

- Allows for easy access to hay storage. Look to match AP-4700 dutch door.

PLYCO CORPORATION  
USA  
800/558-5895  
FAX: 800/257-5926  
INTERNATIONAL  
920/876-3611  
FAX: 920/876-3527  
www.plyco.com



# EQUUS Dutch Door Systems

## MODEL U-4700, UNASSEMBLED DUTCH DOOR

Unassembled 16 gauge steel crossbuck and four-piece perimeter frame components are powder coat painted after six stage wash. Available in bone, chocolate, or charcoal. Shipped with galvanized hardware package that includes galvanized strap hinges, doors, barn latch, barrel bolt, catch kit, and assembly hardware. 3/4" OSB/plywood and 29 gauge flat sheet not included.

An economical system that can be assembled in the field using your choice of 3/4" cores with or without steel skins. Kit comes cartoned.

## MODEL EJS-4700, DUTCH DOOR JAMB KIT (OPTIONAL)

The three-piece steel jamb system is powder coat painted with the same high quality urethane as the door system and is pre-punched for quick, accurate, sag-free installation of the door. Not factory punched to match kit door strap hinges. **Extended Jamb Kit is also available.**

## MODEL AP-4350, BALE DOOR

Allows for easy access to hay storage. Look to match AP-4700 dutch door. Same assembly and construction as AP-4700 dutch door above, including same color options. Includes four piece 16 gauge steel jamb kit and all hardware. RO: 49-1/2" x 43-15/16".

## MODEL AP-4700, PRE-ASSEMBLED DUTCH DOOR

16 gauge steel one-piece perimeter door panel frame is assembled over your choice of available colors (see chart) 29 gauge flat steel sheets attached to both sides of 3/4" exterior grade OSB.

Two heavy steel hinges per door panel are powder coat painted to match the door and bolted into the panel with only the hinge knuckle showing, providing a more finished appearance than the old strap style hinge. All hinges are "E" coated for corrosion resistance, then powder coat painted to match the door. The large size of this hinge allows the door panel to open away from building skin or trim. Nylon spacers provide smooth, quiet operation.

Hardware kit includes Black Barn Latch, Catch Kit, Assembly Hardware, and Galvanized Barrel Bolt. The Catch Kit is designed to be horse safe and is self-storing with the door closed.

Door panels and hardware are individually packaged.



## DUTCH DOOR COLORS

Twelve Powder Coat Colors available as well as additional painted colors to match most roll-formers' colors. Specify roll-former when purchasing.

Because of its ongoing commitment to product improvement, Plyco Corporation reserves the right to change, without notice, product specifications, availability, prices and conditions of sale.

**PLYCO**  
CORPORATION  
PO BOX 386 • ELKHART LAKE, WI 53020

**www.plyco.com 800/558-5895 FAX: 800/257-5926**  
**INTERNATIONAL 920/876-3611 FAX: 920/876-3527**

**WINDOWS • WALK DOORS • WALL VENTS • RIDGE VENTS**  
**SLIDING DOOR TRACK • SLIDE DOOR RAILS • PLY-FOIL INSULATION**  
**HORSE STALLS • FASTENERS & CLOSURES • SPECIALTY PRODUCTS**