

COMBO[®] DOOR TRACK

COMBO sliding door track is self-cleaning and self-aligning. Its unique, flat-top design imparts extra strength to the track which eliminates deflection from heavy, rolling doors. COMBO track is made of 14-gauge, galvanized, high-carbon steel that's roll-formed to assure maximum uniformity over its entire length. 14-gauge, galvanized steel mounting brackets are projection-welded* on top of the track at 2-foot intervals. Mounts with nails or lag bolts. Comes in standard lengths from 8- to 20-feet. Other lengths are available upon request.

Nos. 112081-112202 — COMBO track with top-mount brackets.

No. 119000 — Splice collar.

Locks two track sections together in perfect alignment at the joint. Special design permits back side of the track to bear against the header for extra strength and rigidity.

Nos. 112081
thru 112202

119000

COMBO[®] TROLLEY HANGERS

COMBO trolley hangers are made to handle doors up to 600-pounds. There is no metal-to-metal contact. Tough, ball-shaped, self-lubricating, Delrin-500 trolley wheels roll easily in the round COMBO track and are virtually impervious to wear. Teflon grease is added for even smoother operation. Polished-steel roller-bearings are optional in all trolley wheels for ultimate rolling ease with heaviest doors. Long, underslung wheel bases eliminate chattering and bucking. All metal parts are zinc-plated.

No. 146550 — Roller-bearing, 6½" offset-bolt trolley hanger.

For wood- and metal-frame doors. Swivel stirrup provides up to 180° swing in either direction. Adjust ¼" laterally. Has 5" thread for vertical adjustment with roller-bearing wheels.

146550

Sliding Door Track Accessories

No. 191550 — "Ragland" center latch.

Same as No. 191000, except with heavy-duty latching chain.

191550

No. 188300P — Cam-action jamb latch.

7-inch hook and powerful cam-action pulls the door securely against the jamb. Eliminates rattling and wind damage. Opens inside only. Made of heavy galvanized steel with red, plastic-coated handle.

188300P

No. 183500 — White-painted door pull.

6⅞" x 1¼" size means plenty of room for the largest hand, even when gloved with white-painted finish.

183500


No. 185000 — "Guide-Master" adjustable door stop.

Large, converging surfaces guide the door leaf gently into the stop and hold it securely to avoid wind damage. Mounts wherever needed (even at corners) to stop doors in the open or closed positions. Formed, stationary leg straddles siding ribs... no need to cut siding. Adjusts for 1½" to 3½" doors. Heavy-gauge, zinc-plated steel.

185000

SDR0500GZ-5' GUIDE RAIL SDR1000GZ-10'

- Heavy galvanized steel.
- 5' & 10' lengths - use length or lengths equal to 1/3 - 1/2 the door panel width or more if desired.
- Bracket mounting hole located to allow lead in when door is closed and to aid in installation over metal or other obstruction.
- Holds door down and in.



Note: Guide System is designed to give 4¼" of in/out and 2¼" of up/down adjustment.

SDR1635BR BOTTOM RAIL

- Dual purpose - attaches to wood or steel girt.
- 18 gauge steel.
- Bottom rail channel mates w/guide rail system.
- Available 8', 10', 12' lengths.

